

PRODUCTS SPECIFICATION

5050 SMD RIGID BAR SERIES

For LD-RD-A5050-12-30

Made by	Checked by	Version
Mustafa	Lucy	2009.2.4



30 LED Rigid bar introduction.

Features:

Available in DC12V maximum.

Very bright & low power consumption.


Operating temperature: -20~50C°.

Long life span LED lights, more than 50,000 hours +.

Dimmable to 6V DC.

Water-proof, IP67.

Photos:



Assembly drawing


Top View



Section



3D View




View Angle: 120degrees

Operation Temperature: -20°C~50°C


Store Temperature: -30°C~80°C


5050 SMD LED Rigid bar: 30 LED/meter




These strips are widely used in shop and bar illumination, it works at 12DC, with super bright SMD LEDs, wide view angle, compact size, easy to install, Aluminium PCB holder help you to fix easily. Water-proof, long life span(more than 50000 hours),

Aluminium series: 5050 30LED/meter						
Part number	Color	Size	LED QTY/meter	Lumen/meter	Voltage	Power/meter
LD-RD-A5050RGB-12-30	Red	100mm	30	60	DC12 V	7.5 watt
	Green	100mm		120		
	Blue	100mm		75		
LD-RD-A5050R-12-30	Red	100mm	30	180	DC12 V	7.5 watt
LD-RD-A5050Y-12-30	Yellow	100mm	30	180	DC12 V	7.5 watt
LD-RD-A5050B-12-30	Blue	100mm	30	225	DC12 V	7.5 watt
LD-RD-A5050G-12-30	Green	100mm	30	360	DC12 V	7.5 watt
LD-RD-A5050W-12-30	White	100mm	30	450	DC12 V	7.5 watt
LD-RD-A5050WW-12-30	Warm white	100mm	30	360	DC12 V	7.5 watt
LD-RD-A5050P-12-30	Pink	100mm	30	180	DC12 V	7.5 watt






for: red, blue, green, yellow



for: white LED

How to connect RGB rigid bar.

Below shows you how to connect the RGB Rigid bar to power supplies.



How to connect single color rigid bar.

Below shows you how to connect the single color Rigid bar to power supplies.

